



POWER DISTRIBUTION CENTERS

THE NEXT GENERATION OF TEMPORARY POWER



PDC AS SHOWN

- Supply Pigtail: 20' 2/4 Type "W" Extra-Hard-Usage Cable
- Input: 100 Amp 480 Volt 3 Phase
- Output: 225 Amp 208Y/120 Volt 3 Phase
- Energy Efficient 75 KVA Transformer Allows use of Over 24 Tempower Boxes
- 4-20 Amp 125 Volt Spec Grade GFCI Receptacles w/LED Indicating Light
- 2-30 Amp 250 Volt Locking Receptacles
- 8-50 Amp 125/250 Volt Heavy Duty CS-Style Locking Receptacles (for Tempower Boxes)
- Oversize Foam Filled 10" Pneumatic Wheels Provide for Easy Maneuverability 2-Rigid and 2-Swivel Locking
- Dimensions Approx. 34"W X 56"L X 53"H
- Weighs Approx. 900 Lbs.

INNOVATION

- Compact Design Allows Passage Through 3'0" Doorway
- Versatile Skid Base Allows Lifting Through Forklift Pockets
 - *Tie Down/Picking Eyes Available (Not Shown)
 - *Protective Cages Available (Not Shown)
- Streamline Stainless Steel Flush Folding Locking "T" Handle
- Connect 4 Wires and your Plug Together System is Ready to Use
- Robust Outdoor Design
- Various Configurations and Options Readily Available

QUALITY

- Rugged Exterior Grade Powder Coat Finish
- Weather Resistant Metal Flip Covers
- Assembled with Stainless Steel Hardware
- Double Roller 3-Point Latching and Locking Mechanism Secures Door
- Main Circuit Breaker Copper Bus Panelboard

SAFETY

- All High Quality UL Listed Components
- All Wiring Meets or Exceeds National Electric Code (NEC) and UL Standards
- 480 Volt Main Disc Switch Features Lock-Out Mechanism for Added Protection
- Full Dead-Front Panel Covers Protects All Personnel from Live Parts
- Exterior High Contrast Engraved Labels
- Oversize Single-Point Grounding System



SPEC, LLC

Seattle, WA • USA

Email: jeffjohnson.wa@netzero.net

Tel: 425.402.8332 • Fax: 425.402.8424

Visit our Website at www.tempower.net

For Further Information Call:

1.888.722.0243

